Eaton 56ET

Catalog Number: 56ET

Eaton Bussmann series high speed British standard fuse, Single barrel, 56A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

General specifications



291.018 cm³

Catalog Number

Eaton Bussmann series high speed

british standard fuse

56ET

Packing Unit Case Pack

SAP-UNITY

Pack

EAN Quantity

 5027590354127
 480

 5027590049818
 10

Gross Weight Length

20.456 kg 385 mm 0.414 kg 82 mm

Width Height

280 mm 175 mm 91 mm 39 mm

Volume ERP Name 18865 cm³ SAP-UNITY

Product Length/Depth Product Height

76 mm 20 mm

Product Width Product Weight

20 mm 41.4 g





Compliances

Certifications

CE Marked **UL** Recognized

Electrical data

Amperage Rating

56 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

500 V

Interrupt rating

200 kA RMS Sym, 50 kA at 500 Vdc

Class

Class aR

Pre arc (I2T)

135

Clearing (I2T)

950

Watt losses

11 W

Product specifications

Designed and tested to B588 part 4

Application

IEC 60269-4

Semiconductor, DC Common bus, DC drives, power

converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

eaton-bussmann-series-bs88-high-speed-fuses-product-aid-

pal35003en-us.pdf

Catalogs

IEC high speed fuse links

Certification reports

DA-DC-00004682

DA-DC-00004685

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.







