

Eaton 630LMMT

Catalog Number: 630LMMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 630A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 150 VDC (IEC). 50 kA at 150 VDC (UL)



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	630LMMT
	Packing Unit
	Case Pack
EAN	Quantity
5027590357272	36
Gross Weight	Length
13.832 kg	385 mm
Width	Height
280 mm	175 mm
Volume	ERP Name
18865 cm ³	SAP-UNITY
Product Length/Depth	Product Height
84 mm	83 mm
Product Width	Product Weight
38 mm	368 g
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized
	Designed and tested to BS88 part 4
	UL recognized

IEC 60269-4

CCC

Electrical data

Amperage Rating

630 A

Voltage rating

240 Vac, 150 Vdc

Rated voltage AC

240 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 40 kA at 150 Vdc (IEC)

200 kA RMS Sym, 50 kA at 150 Vdc (UL)

Class

Class aR

Pre arc (I2T)

24000

Clearing (I2T)

150000

Watt losses

75 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-250 Trip indicator kit (indicator + clips)

TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogs

[IEC high speed fuse links](#)

Certification reports

DA-DC-00004685

DA-DC-00004682

Technical data sheets

720004 LCT, LET, LMMT, LMT



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)