

Eaton 6H07-660

Catalog Number: 6H07-660

Fuse-link, low voltage, 6 A, AC 690 V, DC 460 V, BS88/A2, 22 x 82 mm, gL/gG, BS

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	6H07-660
	UPC
	051712674348
EAN	Product Length/Depth
5027590486262	84.5 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
47.75 g	Not Applicable
Compliances	
Contact Manufacturer	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

6 A

Fitted with:

Offset bolted tags

Fuse size

BS88/A2

Current type

AC/DC

Mounting dimension

M5

Center-to-center distance of connections

71.5 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

690 V

Rated voltage DC

460 V

Class

Class gG/gL

Fuse type

H07-660

Utilization category

gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA BS88-2 660V Industrials, H07-660

CE BS88-2 660V Industrials, H07-660

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4150 H07-660 fuses

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

3.3 W

Connection

Bolt-on

Construction

BS88/A2

Construction size

A2

Fuse shape

Offset bolted tags

Voltage type

AC/DC

Voltage rating

690 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)