Eaton 71FE

Catalog Number: 71FE

Eaton Bussmann series high speed British standard fuse, Single barrel, 71A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

General specifications

Product Name Eaton Bussmann series high speed british standard fuse

EAN 5027590354639 5027590055000

Gross Weight

15.7 kg

0.405 kg

Width

280 mm 91 mm

Volume

18865 cm³ 2910.18 cm³

Product Length/Depth 82 mm

Product Width 91 mm Catalog Number 71FE Packing Unit Case Pack Pack Quantity 360 10 Length 385 mm 82 mm Height 175 mm 39 mm

ERP Name

SAP-UNITY SAP-UNITY

Product Height 39 mm

Product Weight 40.5 g





Compliances

CE Mar	ked
Electrical data	^{pliar} Product specifications
Amperage Rating	Application
71 A	Semiconductor, DC Common bus, DC drives, power
Voltage rating	converters/rectifiers
690 V (IEC), 700 V (UL)	Fuse indicator
Rated voltage AC	None
690 V	
Rated voltage DC	Compatble Trip indicator/Microswitch
500 V	Suitable for
Interrupt rating	EC-600 Trip indicator kit (indicator + clips)
200 kA RMS Sym, 50 kA at 500 Vdc	TI700 Fuse indicator
Class	MAI Microswitch/adaptor
Class aR	MBI Microswitch/adaptor
Pre arc (I2T)	
210	Resources
Clearing (I2T)	Brochures
600 at 415 V, 950 at 660 V	eaton-bussmann-series-bs88-high-speed-fuses-product-aid-
Watt losses	pal35003en-us.pdf
17 W	Catalogs
	IEC high speed fuse links
	Certification reports
	DA-DC-00004685
	DA-DC-00004682
	Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

© 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia