# **Eaton 7::20HGMA160**

### Catalog Number: 7.20HGMA160

Oil fuse-link, medium voltage, 160 A, AC 7.2 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker

#### General specifications

Product Name

Catalog Number

Eaton Bussmann series medium voltage 7.20HGMA160

oil fuse

Model Code

7.2KV 160A 2.5" OIL FUSE

**UPC** 

051712585378

EAN

5027590488228

Product Length/Depth

**Product Height** 

359 mm

63.5 mm

**Product Width** 

**Product Weight** 

63.5 mm

2600 g

Warranty

Compliances

Not Applicable

BS 2692-1 ESI 12-8

201

Certifications

IEC Rated

IEC60282-1





#### Resources

## default Taxonomy Attribute LabelType fuse Application protection of primary side transformer, and oil-filled fuse switch combination unit **Amperage Rating** 160 A Fuse indicator with striker Fuse size 63.5 x 359 mm Breaking capacity 45 kA Installation technique Oil Performance Cat According To IEC 60282-1 Back-up **Product application** Primary side transformer protection Rated frequency - max 60 Hz Rated frequency - min 50 Hz Release characteristic Other Standard **British Standard** Utilization category Other Voltage type AC With striker Yes Fuse diameter

63.5 mm

Joule integral (I2T) - max operating

1.8 x 105

Joule integral (I2T) - min pre-arcing

1.3 x 104

Resistance

3.81

Class

Class back-up

**Barrels** 

1

Construction type

F02/BS 2692

Fuse shape

Cylindrical

Interrupt rating

40 kAIC

45 kAIC

Construction size

63.5 x 359 mm

Voltage rating

7.2 kV

Fuse type

**OHGM** 



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia