

# Eaton 7::2TDLSJ16

Catalog Number: 7.2TDLSJ16

Eaton Bussmann series medium voltage DIN fuse, 16 A, 7.2 kV, 40 kA, 51 x 292 mm, With Striker

## General specifications



Photo is representative

Product Name	Catalog Number
Eaton Bussmann series medium voltage DIN fuse	7.2TDLSJ16
	UPC
	051712185943
EAN	Product Length/Depth
5027590488303	292 mm
Product Height	Product Width
51 mm	51 mm
Product Weight	Warranty
1630 g	Not Applicable
Compliances	
DIN 43625	
VDE 0670-4	
IEC 60282-1	

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

transformer protection  
indoor or outdoor use

### Amperage Rating

16 A

### Fuse indicator

With Striker

### Fuse size

51 x 292 mm

### Breaking capacity

40 kA

### Installation technique

Air

### Performance Cat According To IEC 60282-1

Back-up

### Product application

Primary side transformer protection

### Rated frequency - max

50 Hz

### Rated frequency - min

50 Hz

### Release characteristic

Other

### Standard

DIN

### Utilization category

Other

### Voltage type

AC

### With striker

Yes

### Class

Class back-up

## Resources

### Catalogs

7.2TDLSJ16~7-2TDLSJ16~7.2KV 16Amp 2 DIN Sealed Fuse

Bussmann series complete full line catalog no. 1007

### Technical data sheets

720105 17.5kV DIN medium voltage fuses

720106 24kV DIN medium voltage fuses

720103 7.2kV DIN medium voltage fuses

720104 12kV DIN medium voltage fuses

## Barrels

1

## Used with

270303 Fuse clip

A3354710 Fuse clip

## Pre arc (I2T)

5.5 x 100

## Resistance

65.1 Ohms

## Watt losses

23 W

## Fuse diameter

51 mm

## Interrupt rating

40 kAIC

## Construction size

51 x 292 mm

## Mounting method

Clip-in

## Packaging type

Standard

## Voltage rating

7.2 kV

## Fuse type

TDLSJ



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)