

Eaton 7::2TDLSJ20

Catalog Number: 7.2TDLSJ20

Eaton Bussmann series medium voltage DIN fuse, 20 A, 7.2 kV, 40 kA, 51 x 292 mm, With Striker

General specifications



Photo is representative

Product Name	Catalog Number
Eaton Bussmann series medium voltage DIN fuse	7.2TDLSJ20
	UPC
	051712185950
EAN	Product Length/Depth
5027590488327	292 mm
Product Height	Product Width
51 mm	51 mm
Product Weight	Warranty
1630 g	Not Applicable
Compliances	
DIN 43625	
VDE 0670-4	
IEC 60282-1	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

transformer protection
indoor or outdoor use

Amperage Rating

20 A

Fuse indicator

With Striker

Fuse size

51 x 292 mm

Breaking capacity

40 kA

Installation technique

Air

Performance Cat According To IEC 60282-1

Back-up

Product application

Primary side transformer protection

Rated frequency - max

50 Hz

Rated frequency - min

50 Hz

Release characteristic

Other

Standard

DIN

Utilization category

Other

Voltage type

AC

With striker

Yes

Class

Class back-up

Resources

Catalogs

7.2TDLSJ20~7-2TDLSJ20~7.2KV 20Amp 2 DIN Sealed Fuse

Bussmann series complete full line catalog no. 1007

Technical data sheets

720104 12kV DIN medium voltage fuses

720103 7.2kV DIN medium voltage fuses

720105 17.5kV DIN medium voltage fuses

720106 24kV DIN medium voltage fuses

Barrels

1

Used with

270303 Fuse clip

A3354710 Fuse clip

Pre arc (I2T)

9.7 x 100

Resistance

48.9 Ohms

Watt losses

27 W

Fuse diameter

51 mm

Interrupt rating

40 kAIC

Construction size

51 x 292 mm

Mounting method

Clip-in

Packaging type

Standard

Voltage rating

7.2 kV

Fuse type

TDLSJ



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia