



## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

transformer protection  
indoor or outdoor use

### Amperage Rating

80 A

### Fuse indicator

With Striker

### Fuse size

76 x 292 mm

### Breaking capacity

40 kA

### Installation technique

Air

### Performance Cat According To IEC 60282-1

Back-up

### Product application

Primary side transformer protection

### Rated frequency - max

50 Hz

### Rated frequency - min

50 Hz

### Release characteristic

Other

### Standard

DIN

### Utilization category

Other

### Voltage type

AC

### With striker

Yes

### Class

Class back-up

## Resources

### Catalogs

Bussmann series complete full line catalog no. 1007

7.2TFLSJ80~7-2TFLSJ80~7.2KV 80Amp 3 'J' DIN Fuse

### Technical data sheets

720104 12kV DIN medium voltage fuses

720103 7.2kV DIN medium voltage fuses

720105 17.5kV DIN medium voltage fuses

720106 24kV DIN medium voltage fuses

Barrels

1

Used with

270303 Fuse clip

A3354730 Fuse clip

Pre arc (I2T)

5 x 1000

Resistance

61 Ohms

Watt losses

54 W

Fuse diameter

76 mm

Interrupt rating

40 kAIC

Construction size

76 x 292 mm

Mounting method

Clip-in

Packaging type

Standard

Voltage rating

7.2 kV

Fuse type

TFLSJ



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia