

Eaton 80NHG000B

Catalog Number: 80NHG000B

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 500V, 80A, 120 kAIC, Combination fuse status indicator, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Metal plated copper contact plate, Ceramic body

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	80NHG000B
	EAN
	5027590490726
UPC	Product Length/Depth
051712625852	79 mm
Product Height	Product Width
51 mm	21 mm
Product Weight	Compliances
119.333 g	CE Marked
	RoHS Compliant
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	



Electrical data

Amperage Rating

80 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

120 kA

Class

Class gG/gL

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH000

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

Microswitch 170H0236

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

EBH Size 000 Horizontal fuse switch-disconnectors

Resources

Catalogues

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[NH Fuse links, bases and gear](#)

[CA134002EN](#)

Compliance information

[CE NH Size 000, 500V fuse-links](#)

[UKCA NH Size 000, 500V fuse-links](#)

Multimedia

[Eaton Bussmann – NH fuse link portfolio](#)

Presentations

[NH Overview Video](#)

Technical data sheets

[10164 NH 500 Volts gG](#)

Technical service bulletins

[Datasheet - 80NHG000B](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)