

Eaton AAO4

Catalog Number: AAO4

Fuse-link, LV, 4 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS



General specifications

| | |
|--|-----------------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series low voltage british standard fuse | AAO4 |
| | UPC |
| | 051712838474 |
| EAN | Product Length/Depth |
| 5027590491617 | 85 mm |
| Product Height | Product Width |
| 14 mm | 14 mm |
| Product Weight | Warranty |
| 20.1 g | Not Applicable |
| Compliances | |
| RoHS Compliant | |

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

4 A

Fitted with:

Offset bolted tags

Fuse size

BS88/A2

Current type

AC

Mounting dimension

M5

Center-to-center distance of connections

73 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

550 V

Class

Class gG/gL

Fuse type

AAO

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

CE AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4109 AAO fuses

No

Watt losses

1.4 W

Connection

73 mm fixing centre

Construction

BS88/A2

Construction size

A2

Fuse shape

Offset bolted tags

Voltage type

AC

Suitable for

CM32F Camaster fuse holder

RS32 Red spot fuse holder

Quantity

20

Voltage rating

550 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia