Eaton BAF-5

Catalog Number: BAF-5

Eaton Bussmann series BAF fuse, Fast acting, 5 A, Non-indicating, Ferrule end x ferrule end, 10 kAIC at 125 Vac|200 AIC at 250 Vac, Nickel-plated brass endcaps, Standard, 250 V

General specifications

| Bussman 250Vac Fast-acting Fuse |
|--|
| BAF |
| m |

Photo is representative

| Product Name | Catalog Number |
|--------------------------------|----------------|
| Eaton Bussmann series BAF fuse | BAF-5 |
| UPC | EAN |
| 051712320054 | 5027590056854 |
| Product Length/Depth | Product Height |
| 0.41 in | 1.5 in |
| Product Width | Product Weight |
| 0.41 in | 0.25 lb |
| Warranty | Compliances |
| Not Applicable | CE Marked |



Electrical rating

Amperage Rating

5 A

Interrupt rating

10 kAIC at 125 Vac 200 AIC at 250 Vac

Voltage rating 250 V

Physical details

Material

Nickel-plated brass endcaps

Packaging type

Standard

General information

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Silver-plated fuse caps, replacement for "F15B" fuses

Resources

Catalogs Bussmann series complete full line catalog no. 1007

Multimedia Bussmann series Fuseology

Specifications and datasheets Eaton Specification Sheet - BAF-5

Technical data sheets BAF-5~BUSS MIDGET FUSE

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia