

Eaton BAO35

Catalog Number: BAO35

Fuse-link, LV, 35 A, AC 500 V, BS88/A3, 21 x 87 mm, gL/gG, BS

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	BAO35
	EAN
	5027590491969
Product Length/Depth	Product Height
87 mm	22.3 mm
Product Width	Product Weight
22.3 mm	53.2 g
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

35 A

Fitted with:

Offset bolted tags

Fuse size

BS88/A3

Current type

AC

Mounting dimension

M5

Center-to-center distance of connections

73.5 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

BAO

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

Resources

Catalogs

CA134002EN

Compliance information

CE AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

UKCA AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical service bulletins

Datasheet - BAO35

No

Connection

74 mm Fixing Centre

Construction

BS88/A3

Construction size

A3

Fuse shape

Offset bolted tags

Voltage type

AC

Voltage rating

500 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)