

Eaton BAO40

Catalog Number: BAO40

Fuse-link, LV, 40 A, AC 500 V, BS88/A3, 21 x 87 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	BAO40 UPC 051712838542
EAN	Product Length/Depth
5027590491976	87 mm
Product Height	Product Width
21 mm	21 mm
Product Weight	Warranty
50.4 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	IEC 60269-2 BS88

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

40 A

Fitted with:

Offset bolted tags

Fuse size

BS88/A3

Current type

AC

Mounting dimension

M5

Center-to-center distance of connections

73.5 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

BAO

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

CE AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4112 BAO fuses

No

Watt losses

4.7 W

Connection

74 mm Fixing Centre

Construction

BS88/A3

Construction size

A3

Fuse shape

Offset bolted tags

Voltage type

AC

Suitable for

CM63F Camaster fuse holder

RS63 Red spot fuse holder

Voltage rating

500 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)