

# Eaton C10G10

Catalog Number: C10G10

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 10 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage cylindrical fuse	C10G10
	<b>Model Code</b>
	CYLINDRICAL FUSE 10 x 38 10A GG 500V AC
<b>UPC</b>	<b>EAN</b>
051712754262	5027590493390
<b>Product Length/Depth</b>	<b>Product Height</b>
38 mm	10 mm
<b>Product Width</b>	<b>Product Weight</b>
10 mm	8.2 g
<b>Warranty</b>	<b>Compliances</b>
1 year limited	CE Marked
	GoST-R
	RoHS Compliant
<b>Certifications</b>	
IEC 60269	

## defaultTaxonomyAttributeLabel

### Type

fuse

### Application

for industrial applications  
for general purpose use

### Amperage Rating

10 A

### Fuse size

10 x 38 mm

### Current type

AC

### Breaking capacity

120 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Rated voltage AC

500 V

### Class

Class C gL/gG

### Fuse type

C10G

### Utilization category

gG (cable protection/equipment protection)

### Fuse indicator

Other

### Watt losses

1 W

### Connection

Ferrule end x ferrule end

### Construction size

10 mm x 38 mm

### Fuse shape

## Resources

### Catalogs

CA134002EN

Busmann series complete full line catalog no. 1007

### Compliance information

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

### Technical data sheets

720115 Cylindrical fuses

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)