

# Eaton C10G4

Catalog Number: C10G4

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 4 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage cylindrical fuse	C10G4
	<b>EAN</b>
	5027590493543
<b>UPC</b>	<b>Product Length/Depth</b>
051712754231	38 mm
<b>Product Height</b>	<b>Product Width</b>
10 mm	10 mm
<b>Product Weight</b>	<b>Compliances</b>
8.2 g	CE Marked
	GoST-R
	RoHS Compliant
<b>Certifications</b>	
IEC 60269	

## Electrical data

### Amperage Rating

4 A

### Voltage rating

500 V

### Voltage type

AC

### Breaking capacity

120 kA

### Utilization category

gG (cable protection/equipment protection)

### Frequency rating - max

62 Hz

## Compatible fuse holder

### Suitable for

CHM Modular fuse holder

## Resources

### Catalogues

CA134002EN

### Compliance information

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

### Multimedia

Video Cylindrical fuse link portfolio

### Technical data sheets

720115 Cylindrical fuses

### Technical service bulletins

Datasheet - C10G4



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia