

# Eaton C22G100

Catalog Number: C22G100

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 100 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder

## General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C22G100
	EAN
	5027590495196
UPC	Product Length/Depth
051712754514	58 mm
Product Height	Product Width
22.2 mm	22.2 mm
Product Weight	Compliances
55.3 g	CE Marked
	GoST-R
	RoHS Compliant
Certifications	
IEC 60269	

## Electrical data

### Amperage Rating

100 A

### Voltage rating

500 V

### Voltage type

AC

### Breaking capacity

120 kA

### Utilization category

gG (cable protection/equipment protection)

### Frequency rating - max

62 Hz

## Compatible fuse holder

### Suitable for

CH22 Modular fuse holder

## Resources

### Catalogues

CA134002EN

### Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

### Multimedia

Video Cylindrical fuse link portfolio

### Technical data sheets

720115 Cylindrical fuses

### Technical service bulletins

Datasheet - C22G100



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia