

# Eaton C22G125

Catalog Number: C22G125

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 125 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage cylindrical fuse	C22G125
	<b>Model Code</b>
	CYLINDRICAL FUSE 22 x 58 125A gG 500V AC
<b>EAN</b>	<b>UPC</b>
5027590495257	051712589932
<b>Product Length/Depth</b>	<b>Product Height</b>
58 mm	22.2 mm
<b>Product Width</b>	<b>Product Weight</b>
22.2 mm	55.9 g
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

## Electrical data

### Amperage Rating

125 A

### Voltage rating

500 V

### Voltage type

AC

### Breaking capacity

120 kA

### Utilization category

gG (cable protection/equipment protection)

### Frequency rating - max

62 Hz

## Compatible fuse holder

### Suitable for

CH22 Modular fuse holder

## Resources

### Catalogues

CA134002EN

### Compliance information

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

### Multimedia

Video Cylindrical fuse link portfolio

### Technical data sheets

720115 Cylindrical fuses

### Technical service bulletins

Datasheet - C22G125



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia