

Eaton C22G16

Catalog Number: C22G16

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 16 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C22G16
	Model Code
	CYLINDRICAL FUSE 22 x 58 16A GG 690V AC
UPC	EAN
051712754439	5027590495295
Product Length/Depth	Product Height
58 mm	22.2 mm
Product Width	Product Weight
22.2 mm	53.5 g
Warranty	Compliances
No warranty	RoHS Compliant CE Marked
Certifications	
IEC 60269	

defaultTaxonomyAttributeLabel

Type

fuse

Special features

Toll free

Application

for industrial applications
for general purpose use

Amperage Rating

16 A

Fuse size

22 x 58 mm

Current type

AC

Breaking capacity

80 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

690 V

Class

Class C gL/gG

Fuse type

C22G

Used with

Bussmann's modular fuse holders

Utilization category

gG (cable protection/equipment protection)

Fuse indicator

Other

Watt losses

2.1 W

Connection

Resources

Catalogs

CA134002EN

Compliance information

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Ferrule end x ferrule end

Construction size

22 mm x 58 mm

Fuse shape

Cylindrical

Voltage type

AC

Suitable for

CH22 Modular fuse holder

Material

Ceramic

Mounting method

22 x 58 mm CH Modular fuse holder

Packaging type

Standard

Release characteristic

Other

Quantity

10

Voltage rating

690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)