

# Eaton C22G4

Catalog Number: C22G4

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 4 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage cylindrical fuse	C22G4
	<b>UPC</b>
	051712667296
<b>EAN</b>	<b>Product Length/Depth</b>
5027590495424	58 mm
<b>Product Height</b>	<b>Product Width</b>
22.2 mm	22.2 mm
<b>Product Weight</b>	<b>Warranty</b>
53.6 g	1 year limited
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

## defaultTaxonomyAttributeLabel

### Type

fuse

### Application

for industrial applications  
for general purpose use

### Amperage Rating

4 A

### Fuse size

22 x 58 mm

### Current type

AC

### Breaking capacity

80 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Rated voltage AC

690 V

### Class

Class C gL/gG

### Fuse type

C22G

### Utilization category

gG (cable protection/equipment protection)

### Fuse indicator

Other

### Watt losses

1.1 W

### Connection

Ferrule end x ferrule end

### Construction size

22 mm x 58 mm

### Fuse shape

## Resources

### Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

### Compliance information

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

### Technical data sheets

720115 Cylindrical fuses

Cylindrical

Voltage type

AC

Suitable for

CH22 Modular fuse holder

Material

Ceramic

Mounting method

22 x 58 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

690 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)