

# Eaton C22G63

Catalog Number: C22G63

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 63 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage cylindrical fuse	C22G63
	<b>Model Code</b>
	CYLINDRICAL FUSE 22 x 58 63A GG 690V AC
<b>EAN</b>	<b>UPC</b>
5027590495523	051712754491
<b>Product Length/Depth</b>	<b>Product Height</b>
58 mm	22.2 mm
<b>Product Width</b>	<b>Product Weight</b>
22.2 mm	54.8 g
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

## Electrical data

### Amperage Rating

63 A

### Voltage rating

690 V

### Voltage type

AC

### Breaking capacity

80 kA

### Utilization category

gG (cable protection/equipment protection)

### Frequency rating - max

62 Hz

## Compatible fuse holder

### Suitable for

CH22 Modular fuse holder

## Resources

### Catalogues

CA134002EN

### Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

### Multimedia

Video Cylindrical fuse link portfolio

### Technical data sheets

720115 Cylindrical fuses

### Technical service bulletins

Datasheet - C22G63



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia