

Eaton CEO32

Catalog Number: CEO32

Fuse-link, LV, 32 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	CEO32
	EAN
	5027590496285
UPC	Product Length/Depth
051712839457	109.5 mm
Product Height	Product Width
24.5 mm	21 mm
Product Weight	Compliances
77.6 g	CE Marked
	RoHS Compliant
Certifications	
BS88	
IEC 60269	
EAC	



Electrical data

Amperage Rating

32 A

Voltage rating

500 V

Voltage type

AC

Breaking capacity

80 kA

Class

Class gG/gL

Compatible fuse holder

Suitable for

RS100 Red spot fuse holder

Product specifications

Fuse type

CEO

Fitted with:

Offset bolted tags

Construction

BS88/A4

Resources

Catalogues

CA134002EN

Compliance information

CE AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

UKCA AAO,BAO,CEO,NITD,NIT,GTIS,CEO100M,GTIS63M

Installation videos

Video BS88 industrial fuse links

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4115 CEO fuses

Technical service bulletins

Datasheet - CEO32



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)