

# Eaton CH223DIU

Catalog Number: CH223DIU

Eaton's Bussmann series 3-Pole modular fuse holder, rated at 690 V a.c./1000 V d.c. (IEC), 700 V a.c. (UL) , 125 Amps (IEC), 100 A (UL), fitted with a neon indicator, suitable for 22 x 58 mm Cylindrical fuses



## General specifications

|   |                                     |
|---|-------------------------------------|
| <b>Product Name</b>                                       | <b>Catalog Number</b>               |
| Eaton Bussmann series low voltage cylindrical fuse holder | CH223DIU                            |
|   | <b>Model Code</b>                   |
|   | 3P 22x58 Neon Indicator Fuse Holder |
| <b>UPC</b>  | <b>EAN</b>                          |
| 051712685405  | 5027590497114                       |
| <b>Product Length/Depth</b>                               | <b>Product Height</b>               |
| 77 mm   | 123 mm                              |
| <b>Product Width</b>                                      | <b>Product Weight</b>               |
| 107 mm  | 559.5 g                             |
| <b>Compliances</b>  | <b>Certifications</b>               |
| CE Marked   | IEC 60269-2                         |
| RoHS Compliant  | EAC                                 |
|   | IEC 60269-1                         |
|   | UL Listed File E14853               |

## defaultTaxonomyAttributeLabel

### Type

fuse accessory

### Application

Industrial and Commercial applications

### Amperage Rating

125 A

### Number of Poles

Three-pole

### Width in number of modular spacings

6

### Built-in depth

51.5 mm

### Fitted with:

Neon indicator

### Fuse size

22 x 58 mm

### Operating temperature details

-20°C to +70°C

### Voltage rating at AC

690 V a.c. (IEC) and 700 V a.c. (UL)

### Voltage rating at DC

1000 V d.c. (IEC)

### Fuse type

C22G

C22M

### Used with

C22G, C22M, FWP-(amps)A22F fuses

### Lockable

Yes

### Accessories

JV-L Multipole connector kit, CH22-CTP IP20 Protection accessory, CH22-TPS Microswitch to work with CH223D(I)U

### Torque rating

Min 4 Nm/ Max 5 Nm

### Concurrently switching N-neutral

## Resources

### Catalogs

CA134002EN

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

### Compliance information

[CE Modular fuse-holders](#)

[UKCA Modular fuse-holders](#)

### Multimedia

[Eaton Bussmann – Modular fuse holders](#)

### Technical data sheets

[720147 10 x 38 mm Modular fuse holder](#)

[10115 22 x 58 mm Modular fuse holder](#)

[10080 14 x 51 mm Modular fuse holder](#)

No

Material

Polyester

Optical defect indication

Yes

Mounting method

DIN rail

2 x M4 Panel mounting screws

Degree of protection

IP20

Voltage rating

690 V

Model

CH22



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)