

# Eaton CH224DIU

Catalog Number: CH224DIU

Eaton's Bussmann series 4-Pole modular fuse holder, rated at 690 V a.c./1000 V d.c. (IEC), 700 V a.c. (UL) , 125 Amps (IEC), 100 A (UL), fitted with a neon indicator, suitable for 22 x 58 mm Cylindrical fuses

## General specifications



### Product Name

Eaton Bussmann series low voltage cylindrical fuse holder

### EAN

5027590328333

### Product Height

123 mm

### Product Weight

142 g

### Certifications

IEC 60269-2

EAC

IEC 60269-1

UL Listed File E14853

### Catalog Number

CH224DIU

### UPC

051712685467

### Product Length/Depth

77 mm

### Product Width

58 mm

### Compliances

CE Marked

RoHS Compliant

## defaultTaxonomyAttributeLabel

### Application

Industrial and Commercial applications

### Amperage Rating

125 A

### Fitted with:

Neon indicator

### Fuse size

22 x 58 mm

### Operating temperature details

-20°C to +70°C

### Voltage rating at AC

690 V a.c. (IEC) and 700 V a.c. (UL)

### Voltage rating at DC

1000 V d.c. (IEC)

### Fuse type

C22G

C22M

### Used with

C22G, C22M, FWP-(amps)A22F fuses

### Accessories

JV-L Multipole connector kit, CH22-CTP IP20 Protection accessory

### Torque rating

Min 4 Nm/ Max 5 Nm

### Construction size

Other

### Material

Polyester

### Optical defect indication

Yes

### Mounting method

DIN rail

2 x M4 Panel mounting screws

### Degree of protection

IP20

## Resources

### Catalogs

CA134002EN

### Compliance information

CE Modular fuse-holders

UKCA Modular fuse-holders

### Multimedia

Eaton Bussmann – Modular fuse holders

### Technical data sheets

10080 14 x 51 mm Modular fuse holder

720147 10 x 38 mm Modular fuse holder

10115 22 x 58 mm Modular fuse holder

### Technical service bulletins

Datasheet - CH224DIU

Model

CH22



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)