

Eaton FF560

Catalog Number: FF560

Fuse-link, low voltage, 560 A, AC 690 V, DC 400 V, BS88/C2, 74 x 210 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	FF560
	UPC
	051712839914
EAN	Product Length/Depth
5027590019910	209 mm
Product Height	Product Width
74 mm	74 mm
Product Weight	Warranty
1053 g	Not Applicable
Compliances	
RoHS Compliant	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

560 A

Fitted with:

Centre bolted tags

Fuse size

BS88/C2

Current type

AC/DC

Mounting dimension

M10

Center-to-center distance of connections

185 mm

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

690 V

Rated voltage DC

400 V

Class

Class gG/gL

Fuse type

FF

Utilization category

gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

CE CD CD100M FF FG GG GF GH

UKCA CD CD100M FF FG GG GF GH

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4102 FF fuses

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

43 W

Connection

133/184 mm fixing centre

Construction

BS88/C2

Construction size

C2

Fuse shape

Center bolted tags

Voltage type

AC/DC

Voltage rating

690 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)