

Eaton FWA-10A10F

Catalog Number: FWA-10A10F

Eaton Bussmann series FWA high speed fuse, 500 Vac (0.25-6.3A), 500 Vdc (2-5A), 10A, 100 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end



General specifications

| | |
|---|-----------------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series high speed cylindrical fuse | FWA-10A10F |
| | UPC |
| | 051712795203 |
| EAN | Product Length/Depth |
| 5027590499132 | 39 mm |
| Product Height | Product Width |
| 11 mm | 11 mm |
| Product Weight | Warranty |
| 9.1 g | Not Applicable |
| Compliances | Certifications |
| CE Marked RoHS Compliant | UL Recognized |

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

10 A

Accessories

BMM Fuse block
CHM modular fuse holder

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

10 x 38 mm

Class

Class aR

Clearing (I²T)

16

Watt losses

2.7 W

Fuse shape

Cylindrical

Pre arc (I²T)

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Technical data sheets

[720003 FWA](#)

3.6

Interrupt rating

100 kAIC

Connection

Ferrule end x ferrule end

Construction size

10 x 38 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

150 V

Fuse type

FWA-A10F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)