Eaton FWA-25A10F

Catalog Number: FWA-25A10F

Eaton Bussmann series FWA high speed fuse, 500V, 25A, 100 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name

Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWA-25A10F

UPC

051712795234

EAN Product Length/Depth

5027590499200 45 mm

Product Height Product Width

23 mm 63 mm

Product Weight Warranty

9.1 g Not Applicable

Compliances Certifications

CE Marked UL Recognized RoHS Compliant CSA Certified





default Taxonomy Attribute LabelType High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers **Amperage Rating** 25 A Accessories BMM Fuse block CHM modular fuse holder Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Other Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 10 x 38 mm Class Class aR Clearing (I2T) 220 Watt losses

4.9 W

Fuse shape Cylindrical

Pre arc (I2T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Technical data sheets

720003 FWA

Interrupt rating

100 kAIC

Connection

Ferrule end x ferrule end

Construction size

10 x 38 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

150 V

Fuse type

FWA-A10F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

