Eaton FWC-20A10F

Catalog Number: FWC-20A10F

Eaton Bussmann series FWC high speed cylindrical fuse, 500V, 20A, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name

Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWC-20A10F

UPC

051712796460

EAN

5027590499354

Product Length/Depth

38 mm

Product Height

Product Weight

11 mm

11 mm

Warranty

8.8 g

Not Applicable

Certifications

Product Width

Compliances **CE Marked**

CSA Certified

RoHS Compliant

UL Recognized



default Taxonomy Attribute Label

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers **Amperage Rating** 20 A Accessories BMM Fuse block CHM modular fuse holder Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Other Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 10 x 38 mm Class Class aR Clearing (I2T) 260 Watt losses 4.8 W

Fuse shape Cylindrical

Pre arc (I2T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Installation videos

Eaton's Switch disconnectors and Bussmann series fuses for MOEM Applications (brightcove.net)

Technical data sheets

720011 FWC

Interrupt rating

200 kAIC Vac

Connection

Ferrule end x ferrule end

Construction size

10 x 38 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

600 V

Fuse type

FWC-A10F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

