Eaton FWC-6A10F

Catalog Number: FWC-6A10F

Eaton Bussmann series FWC high speed cylindrical fuse, 500 Vac/dc (35-800A only), 6A, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name

5027590499415

Product Height

Product Weight

Compliances

CE Marked

RoHS Compliant

11 mm

9 g

EAN

Eaton Bussmann series high speed cylindrical fuse

FWC-6A10F UPC

051712796415

Catalog Number

Product Length/Depth 38 mm

Product Width 11 mm

Warranty Not Applicable

Certifications

UL Recognized CSA Certified



defaultTaxonomyAttributeLabel

Туре

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

6 A

Accessories

BMM Fuse block CHM modular fuse holder

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min 45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

10 x 38 mm

Class

Class aR

Clearing (I2T)

30

Watt losses

1.5 W

Fuse shape

Cylindrical

Pre arc (I2T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Installation videos

Eaton's Switch disconnectors and Bussmann series fuses for MOEM Applications (brightcove.net)

Technical data sheets 720011 FWC

Interrupt rating

200 kAIC Vac

Connection

Ferrule end x ferrule end

Construction size

10 x 38 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

600 V

Fuse type

FWC-A10F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia