Eaton FWH-002A6F

Catalog Number: FWH-002A6F

Eaton Bussmann series FWH high speed fuse, 500 Vac/dc (35-800A only), 2A, 50 kAIC at 0.25-20A, 20 kAIC at 25-30A, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name

Eaton Bussmann series high speed cylindrical fuse

EAN 5027590499477

Product Height 7 mm

Product Weight 2.8 g

Compliances CE Marked RoHS Compliant UPC 051712796651

Catalog Number FWH-002A6F

Product Length/Depth 33 mm

Product Width 7 mm

Warranty Not Applicable

Certifications CSA Certified UL Recognized





defaultTaxonomyAttributeLabel

Туре

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

2 A

Breaking capacity

50 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Class

Class aR

Clearing (I2T)

3.5 at 500 V

Watt losses

3.2 W

Response time

>30 min at 150%, <30 min at 200%, <= to 10 sec at 300%

Fuse shape

Cylindrical

Pre arc (I2T)

1.3

Interrupt rating 50 kAIC

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Connection

Ferrule end x ferrule end

Construction size

Other 6.3 x 32 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

600 V

Fuse type

FWH-A6F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia