

# Eaton FWH-15A14F

Catalog Number: FWH-15A14F

Eaton Bussmann series FWH high speed fuse, 1000 Vac, 800 Vdc, 15A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed cylindrical fuse	FWH-15A14F
	<b>UPC</b>
	051712370813
<b>EAN</b>	<b>Product Length/Depth</b>
5027590499552	55 mm
<b>Product Height</b>	<b>Product Width</b>
32 mm	73 mm
<b>Product Weight</b>	<b>Warranty</b>
20.3 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

## defaultTaxonomyAttributeLabel

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

15 A

### Accessories

CH14 Modular fuse holder

FW14-PCB

### Breaking capacity

200 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Fuse indicator

Other

### Release characteristic

Other

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Fuse size

14 x 51 mm

### Class

Class aR

### Clearing (I<sup>2</sup>T)

40 at 500 V

### Watt losses

5.5 W

### Fuse shape

Cylindrical

### Pre arc (I<sup>2</sup>T)

## Resources

### Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

### Compliance information

UKCA FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

CE FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

### Technical data sheets

720008 FWH

10

Interrupt rating

50 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

600 V

Fuse type

FWH-A14F



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)