

Eaton FWH-25A14F

Catalog Number: FWH-25A14F

Eaton Bussmann series FWH high speed fuse, 25A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end



General specifications

Product Name

Eaton Bussmann series high speed cylindrical fuse

Catalog Number

FWH-25A14F

Model Code

500V 25A S/COND FERRULE 14 X 51MM

UPC

051712370837

EAN

5027590499590

Product Length/Depth

55 mm

Product Height

32 mm

Product Width

73 mm

Product Weight

20.4 g

Warranty

Not Applicable

Compliances

CE Marked
RoHS Compliant

Certifications

UL Recognized
CSA Certified

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

25 A

Accessories

CH14 Modular fuse holder
FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I²T)

191 at 500 V

Watt losses

7 W

Fuse shape

Cylindrical

Pre arc (I²T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720008 FWH

49

Interrupt rating

50 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

600 V

Fuse type

FWH-A14F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)