Eaton FWH-30A14F

Catalog Number: FWH-30A14F

Eaton Bussmann series FWH high speed fuse, 1000 Vac, 800 Vdc, 30A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name

Catalog Number

Eaton Bussmann series high speed

FWH-30A14F

cylindrical fuse

UPC

051712370844

EAN

Product Length/Depth

5027590499620

55 mm

Product Height

Product Width

32 mm

73 mm

Product Weight

Warranty

20.4 g

Not Applicable

Compliances

Certifications

CE Marked

CSA Certified

RoHS Compliant

UL Recognized



default Taxonomy Attribute Label

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers **Amperage Rating** 30 A Accessories CH14 Modular fuse holder FW14-PCB Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Other Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 14 x 51 mm Class Class aR Clearing (I2T) 232 at 500 V Watt losses 9 W

Fuse shape Cylindrical

Pre arc (I2T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720008 FWH

Interrupt rating

50 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

500 V

Fuse type

FWH-A14F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

