

# Eaton FWH-35B

Catalog Number: FWH-35B

Eaton Bussmann series FWH high speed fuse, 750 Vac, 750 Vdc, 35A, 200 kAIC at 1000 Vac, 50 kAIC at 500 Vdc, None, High speed fuse, Blade end X blade end, Stud



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed cylindrical fuse	FWH-35B
	UPC
	051712795746
<b>EAN</b>	<b>Product Length/Depth</b>
5027590499637	108 mm
<b>Product Height</b>	<b>Product Width</b>
28 mm	90 mm
<b>Product Weight</b>	<b>Warranty</b>
63.8 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	UL Recognized
	CSA Certified

## defaultTaxonomyAttributeLabel

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

35 A

### Breaking capacity

200 kA

### Fuse indicator

Non Indicating

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Rated switching capacity

200 kA

### Rated voltage AC

500 V

### Rated voltage DC

500 V

### Mounting dimension

M8

### Center-to-center distance of connections

60.75 mm

### Current type

AC/DC

### Class

Class aR

### Clearing (I2T)

150

### Watt losses

8 W

## Resources

### Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

#### Fuse shape

Cylindrical, center bolted tags

#### Pre arc (I2T)

34

#### Color

None

#### Interrupt rating

50 kAIC at 500 Vdc

200 kAIC at 1000 Vac

#### Connection

Blade end x blade end

#### Construction size

Other

#### Mounting method

Stud

#### Voltage rating

500 Vac, 500 Vdc

#### Fuse type

FWH-B

#### Fuse system (according to IEC 60269)

Other



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)