Eaton FWH-45B

Catalog Number: FWH-45B

Eaton Bussmann series FWH high speed fuse, 750 Vac, 750 Vdc, 45A, 200 kAIC at 1000 Vac, 50 kAIC at 500 Vdc, None, High speed fuse, Blade end X blade end, Stud

General specifications



Eaton Bussmann series high speed

cylindrical fuse

051712795760

EAN

5027590499668

Product Height

28 mm

Product Weight

64.4 g

Compliances **CE Marked**

Catalog Number

FWH-45B

UPC

Product Length/Depth 108 mm

Product Width

90 mm

Warranty

Not Applicable

Certifications

CSA Certified UL Recognized



default Taxonomy Attribute LabelType High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers **Amperage Rating** 45 A Breaking capacity 200 kA Fuse indicator Non Indicating Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 500 V Rated voltage DC 500 V Current type AC/DC Class Class aR Clearing (I2T) 450 Watt losses 7.5 W

Fuse shape

Pre arc (I2T)

105

Cylindrical, center bolted tags

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Color

None

Interrupt rating

200 kAIC at 1000 Vac 50 kAIC at 500 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Voltage rating

500 Vac, 500 Vdc

Fuse type

FWH-B

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia