

# Eaton FWH-4A14F

Catalog Number: FWH-4A14F

Eaton Bussmann series FWH high speed fuse, 750 Vac, 750 Vdc, 4A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

## General specifications



Photo is representative

### Product Name

Eaton Bussmann series high speed cylindrical fuse

### Catalog Number

FWH-4A14F

### Model Code

500V 4A S/COND FERRULE 14.3 X 50.8MM

### UPC

051712795081

### EAN

5027590499675

### Product Length/Depth

14 mm

### Product Height

14 mm

### Product Width

51 mm

### Product Weight

20.6 g

### Warranty

Not Applicable

### Compliances

CE Marked  
RoHS Compliant

### Certifications

UL Recognized  
CSA Certified

## defaultTaxonomyAttributeLabel

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

4 A

### Accessories

CH14 Modular fuse holder  
FW14-PCB

### Breaking capacity

200 kA

### Frequency rating - max

62 Hz

### Frequency rating - min

45 Hz

### Fuse indicator

Other

### Release characteristic

Other

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Fuse size

14 x 51 mm

### Class

Class aR

### Watt losses

3 W

### Fuse shape

Cylindrical

### Interrupt rating

50 kAIC

### Connection

## Resources

### Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

### Compliance information

UKCA FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

CE FWC-\*A10F,FWH-\*A14F,FWP-\*A14F,FWP-\*A14FI etc

### Technical data sheets

720008 FWH

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

500 V

Fuse type

FWH-A14F



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)