

Eaton FWH-5A14F

Catalog Number: FWH-5A14F

Eaton Bussmann series FWH high speed fuse, 1200V, 5A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWH-5A14F
	Model Code
	500V 5A S/COND FERRULE 14.3 X 50.8MM
UPC	EAN
051712370790	5027590499699
Product Length/Depth	Product Height
55 mm	32 mm
Product Width	Product Weight
73 mm	21.2 g
Warranty	Compliances
Not Applicable	CE Marked RoHS Compliant
Certifications	
CSA Certified UL Recognized	

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

5 A

Accessories

CH14 Modular fuse holder
FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Other

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I²T)

6.4 at 500 V

Watt losses

1.5 W

Fuse shape

Cylindrical

Pre arc (I²T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720008 FWH

1.6

Interrupt rating

50 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Voltage rating

500 V

Fuse type

FWH-A14F



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)