Eaton FWJ-200A

Catalog Number: FWJ-200A

Eaton Bussmann series FWJ high speed fuse, 700 Vac (UL), 690 Vac (IEC), 800 Vdc (5-50A), 200A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse

EAN 5027590021210

Product Height 39 mm

Product Weight 195 g

Compliances CE Marked FWJ-200A UPC 051712796224 Product Length/Depth

Catalog Number

145 mm

Product Width 39 mm

Warranty Not Applicable

Certifications CSA Certified UL Recognized





defaultTaxonomyAttributeLabel

Туре

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

200 A

Breaking capacity

25 kA

Fuse indicator

Non Indicating

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Rated switching capacity

25 A

Rated voltage AC 1000 V

Rated voltage DC

800 V

Mounting dimension

M10

Center-to-center distance of connections

113 mm

Current type AC/DC

Class

Class aR

Clearing (I2T) 80000 at 1000 V

Watt losses 32 W

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Fuse shape

Center bolted tags

Pre arc (I2T)

11700

Color

None

Interrupt rating

25 kAIC (35-200A) 100 kAIC (250-2000A) 50 kAIC at 800 Vdc (35-200A 450-600A)

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating 1000 Vac, 800 Vdc

Fuse type

FWJ-A

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia