

# Eaton FWJ-400A

Catalog Number: FWJ-400A

Eaton Bussmann series FWJ high speed fuse, 700 Vac/dc, 400A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed cylindrical fuse	FWJ-400A
	<b>UPC</b>
	051712796262
<b>EAN</b>	<b>Product Length/Depth</b>
5027590021319	147 mm
<b>Product Height</b>	<b>Product Width</b>
51 mm	51 mm
<b>Product Weight</b>	<b>Warranty</b>
533 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

## defaultTaxonomyAttributeLabel

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

400 A

### Breaking capacity

100 kA

### Fuse indicator

Non Indicating

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC

### Rated switching capacity

100 A

### Rated voltage AC

1000 V

### Rated voltage DC

800 V

### Mounting dimension

Other

### Center-to-center distance of connections

113.8 mm

### Current type

AC/DC

### Class

Class aR

### Clearing (I<sup>2</sup>T)

330000 at 1000 V

### Watt losses

67 W

## Resources

### Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Fuse shape

Center bolted tags

Pre arc (I2T)

47000

Color

None

Interrupt rating

100 kAIC (250-2000A)

450-600A)

25 kAIC (35-200A)

50 kAIC at 800 Vdc (35-200A)

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

1000 V

Fuse type

FWJ-A

Fuse system (according to IEC 60269)

Other