

Eaton FWJ-60A

Catalog Number: FWJ-60A

Eaton Bussmann series FWJ high speed fuse, 700 Vac (UL), 690 Vac (IEC), 800 Vdc (5-50A), 60A, 25 kAIC (35-200A), 100 kAIC (250-2000A), 50 kAIC at 800 Vdc (35-200A, 450-600A), None, High speed fuse, Blade end X blade end, Stud



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWJ-60A
	UPC
	051712796156
EAN	Product Length/Depth
5027590499828	19 mm
Product Height	Product Width
19 mm	127 mm
Product Weight	Warranty
120 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

600 A

Breaking capacity

25 kA

Fuse indicator

Non Indicating

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Rated switching capacity

25 A

Rated voltage AC

1000 V

Rated voltage DC

800 V

Mounting dimension

M8

Center-to-center distance of connections

106.91 mm

Current type

AC/DC

Class

Class aR

Clearing (I²T)

5000 at 1000 V

Watt losses

11 W

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Fuse shape

Cylindrical, center bolted tags

Pre arc (I2T)

670

Color

None

Interrupt rating

450-600A)

50 kAIC at 800 Vdc (35-200A

100 kAIC (250-2000A)

25 kAIC (35-200A)

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

1000 Vac, 800 Vdc

Fuse type

FWJ-A

Fuse system (according to IEC 60269)

Other