Eaton FWL-20A20F

Catalog Number: FWL-20A20F

Eaton Bussmann series high speed traction fuse, 20A, 45 kAIC, Fuse, Class gS



General specifications

Product Name Eaton Bussmann series high speed traction fuse

EAN 5027590499989

Product Height 20 mm

Product Weight 104.2 g

Compliances CE Marked FWL-20A20F UPC 051712570701 Product Length/Depth 127 mm

Catalog Number

Product Width 20 mm

Warranty Not Applicable

Certifications IEC Rated



defaultTaxonomyAttributeLabel

Туре

Fuse

Application

traction

Amperage Rating

20 A

Breaking capacity

50 kA

With striker

No

Voltage type

AC/DC

Utilization category

gL/gG (cable protection/equipment protection)

Release characteristic

Other

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Fuse size

20 x 127 mm

Class

Class gG

Clearing (I2T)

1550 at 750 Vdc

Watt losses

5.9 W

Fuse shape

Cylindrical

Pre arc (I2T)

675

Mounting dimension

Other

Current type

Resources

Catalogs

IEC high speed fuse links

Traction fuse-links

Bussmann series complete full line catalog no. 1007

Compliance information CE FWL-*A20F and FWL-*A20FI

UKCA FWL-*A20F and FWL-*A20FI

AC

Rated voltage AC

1200 V

Rated voltage DC

1000 V

Color

None

Interrupt rating

50 kA at 1000 Vdc

Construction size

Other

Material

Ceramic

Packaging type

Standard

Voltage rating

1200 V

Fuse type

FWL-A20F

Suitable for

CH127 Fuse holder



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia