

Eaton FWP-10A14FI

Catalog Number: FWP-10A14FI

Eaton Bussmann series FWP high speed fuse, 690 Vac (IEC), 700 Vac (UL), 600 Vdc (UL), 10A, 200 kAIC at 700 Vac, 50 kAIC at 600 Vdc, With Indicator, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-10A14FI
	UPC
	051712510738
EAN	Product Length/Depth
5027590500111	52 mm
Product Height	Product Width
15 mm	15 mm
Product Weight	Warranty
20.2 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

10 A

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Top fuse status indicator

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

22

Watt losses

4 W

Fuse shape

Cylindrical

Pre arc (I2T)

4

Used with

Finger safe holders/blocks and striker

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720025 FWP

Color

White

Interrupt rating

200 kAIC

Fitted with:

Striker

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A14FI



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia