Eaton FWP-15A14FI

Catalog Number: FWP-15A14FI

Eaton Bussmann series FWP high speed fuse, 690 Vac (IEC), 700 Vac (UL), 600 Vdc (UL), 15A, 200 kAIC at 700 Vac, 50 kAIC at 600 Vdc, With Indicator, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceremic

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse

EAN 5027590500227

Product Height 15 mm

Product Weight 23.9 g

Compliances CE Marked RoHS Compliant Catalog Number FWP-15A14FI UPC 051712510745 Product Length/Depth 52 mm

Product Width 15 mm

Warranty Not Applicable

Certifications CSA Certified UL Recognized





defaultTaxonomyAttributeLabel

Туре

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

15 A

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator Top fuse status indicator

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

70

Watt losses

5.5 W

Fuse shape

Cylindrical

Pre arc (I2T)

10

Used with

Finger safe holders/blocks and striker

Resources

Catalogs IEC high speed fuse links Bussmann series complete full line catalog no. 1007 Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets 720025 FWP

Color

White

Interrupt rating

200 kAIC

Fitted with:

Striker

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating 700 V

Fuse type

FWP-A14FI



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia