

Eaton FWP-15B

Catalog Number: FWP-15B

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 690 Vac (IEC), 500 Vdc (2-100A), 500 Vac, 15A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-15B
	UPC
	051712557801
EAN	Product Length/Depth
5027590500234	73 mm
Product Height	Product Width
15 mm	15 mm
Product Weight	Warranty
25.3 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

15 A

Breaking capacity

200 kA

Fuse indicator

Non Indicating

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Rated switching capacity

200 A

Rated voltage AC

700 V

Rated voltage DC

700 V

Mounting dimension

M6

Center-to-center distance of connections

63.35 mm

Current type

AC/DC

Class

Class aR

Clearing (I2T)

75 at 700 V

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Technical data sheets

[FWP NA bolted fuse-links](#)

Watt losses

5.5 W

Fuse shape

Center bolted tags

Pre arc (I2T)

10

Color

None

Interrupt rating

200 kAIC Vac

50 kAIC at 700 Vdc

200 kAIC at 300 Vdc

50 kAIC at 300 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other