Eaton FWP-20A14F

Catalog Number: FWP-20A14F

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 700 Vdc (UL), 690 Vac (IEC), 20A, 200 kAIC at 700 Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

General specifications



Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWP-20A14F

UPC

051712795944

EAN Product Length/Depth

5027590500296 51 mm

Product Height Product Width

15 mm 15 mm

Product Weight Warranty

20.2 g Not Applicable

Compliances Certifications

CE Marked UL Recognized RoHS Compliant CSA Certified





defaultTaxonomyAttributeLabel

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage Rating 20 A Accessories CH14 Modular fuse holder FW14-PCB Breaking capacity 200 kA Frequency rating - max 62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

180

Watt losses

6.5 W

Fuse shape

Cylindrical

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720025 FWP

Minimum melting

26 I2t (A2 sec)

Pre arc (I2T)

26

Used with

Finger safe holders/blocks and striker

Color

White

Interrupt rating

200 kAIC Vac 200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A14F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia