

# Eaton FWP-25B

Catalog Number: FWP-25B

Eaton Bussmann series FWP high speed fuse, 700 Vac/dc, 25A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud



## General specifications

|   |                             |
|---|-----------------------------|
| <b>Product Name</b>                               | <b>Catalog Number</b>       |
| Eaton Bussmann series high speed cylindrical fuse | FWP-25B                     |
|   | UPC                         |
|   | 051712557825                |
| <b>EAN</b>  | <b>Product Length/Depth</b> |
| 5027590500500                                     | 73 mm                       |
| <b>Product Height</b>                             | <b>Product Width</b>        |
| 15 mm   | 15 mm                       |
| <b>Product Weight</b>                             | <b>Warranty</b>             |
| 25.4 g  | Not Applicable              |
| <b>Compliances</b>                                | <b>Certifications</b>       |
| CE Marked   | UL Recognized               |
| RoHS Compliant                                    | CSA Certified               |

## defaultTaxonomyAttributeLabel

### Type

High speed fuse

### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

### Amperage Rating

25 A

### Breaking capacity

200 kA

### Fuse indicator

Non Indicating

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC/DC

### Fuse size

22 x 58 mm

### Rated switching capacity

200 A

### Rated voltage AC

700 V

### Rated voltage DC

700 V

### Mounting dimension

M6

### Center-to-center distance of connections

63.35 mm

### Current type

AC/DC

### Class

Class aR

### Clearing (I2T)

340 at 700 V

## Resources

### Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

### Technical data sheets

[FWP NA bolted fuse-links](#)

Watt losses

7 W

Fuse shape

Center bolted tags

Pre arc (I2T)

44

Color

None

Interrupt rating

50 kAIC at 700 Vdc

200 kAIC Vac

200 kAIC at 300 Vdc

50 kAIC at 300 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other