

Eaton FWP-30B

Catalog Number: FWP-30B

Eaton Bussmann series FWP high speed fuse, 1400 Vac (FWS 8-15A), 2100 Vac (FWS 2-6A), 1000 Vdc (FWL/FWS 2-30A), 30A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-30B
	UPC
	051712557832
EAN	Product Length/Depth
5027590500593	73 mm
Product Height	Product Width
15 mm	15 mm
Product Weight	Warranty
24.8 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

30 A

Breaking capacity

200 kA

Fuse indicator

Non Indicating

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Rated switching capacity

200 A

Rated voltage AC

700 V

Rated voltage DC

700 V

Mounting dimension

M6

Center-to-center distance of connections

63.35 mm

Current type

AC/DC

Class

Class aR

Clearing (I2T)

450 at 700 V

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Watt losses

9 W

Fuse shape

Center bolted tags

Pre arc (I2T)

58

Color

None

Interrupt rating

50 kAIC at 700 Vdc

200 kAIC Vac

200 kAIC at 300 Vdc

50 kAIC at 300 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other