Eaton FWP-3A14F

Catalog Number: FWP-3A14F

Eaton Bussmann series FWP high speed fuse, 700V (UL), 3A, 200 kAIC, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

General specifications

Product Name

Eaton Bussmann series high speed cylindrical fuse

EAN 5027590500708

Product Height

15 mm

Product Weight 20.5 g

Compliances CE Marked RoHS Compliant FWP-3A14F UPC 051712795111

Catalog Number

Product Length/Depth 51 mm

Product Width 15 mm

Warranty Not Applicable

Certifications

UL Recognized CSA Certified



Photo is representative



defaultTaxonomyAttributeLabel

Туре

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

3 A

Accessories

CH14 Modular fuse holder FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min 45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

0.26

Watt losses

2.8 W

Fuse shape

Cylindrical

Pre arc (I2T)

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets 720025 FWP

0.11

Used with

Finger safe holders/blocks and striker

Color

White

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A14F



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia