

Eaton FWP-40A14F

Catalog Number: FWP-40A14F

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 700 Vdc (UL), 690 Vac (IEC), 40A, 200 kAIC at 700 Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-40A14F
	Model Code
	40A 700V AC FERRULE 14x51mm
UPC	EAN
051712796507	5027590420631
Product Length/Depth	Product Height
51 mm	15 mm
Product Width	Product Weight
15 mm	20.2 g
Warranty	Compliances
Not Applicable	CE Marked RoHS Compliant
Certifications	
UL Recognized CSA Certified	



defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

40 A

Accessories

CH14 Modular fuse holder
FW14-PCB

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Non Indicating

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

14 x 51 mm

Class

Class aR

Clearing (I2T)

750

Watt losses

8 W

Fuse shape

Cylindrical

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

[CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

Installation videos

[Eaton's Switch disconnectors and Bussmann series fuses for MOEM Applications \(brightcove.net\)](#)

Technical data sheets

[720025 FWP](#)

Minimum melting

84 I2t (A2 sec)

Pre arc (I2T)

84

Used with

Finger safe holders/blocks and striker

Color

White

Interrupt rating

200 kAIC

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A14F