Eaton FWP-40A14FI

Catalog Number: FWP-40A14FI

Eaton Bussmann series FWP high speed fuse, 690 Vac (IEC), 700 Vac (UL), 600 Vdc (UL), 40A, 200 kAIC at 700 Vac, 50 kAIC at 600 Vdc, With Indicator, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceremic





Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWP-40A14FI

UPC

051712542852

EAN Product Length/Depth

5027590500722 52 mm

Product Height Product Width

15 mm 15 mm

Product Weight Warranty

20.4 g Not Applicable

Compliances Certifications

CE Marked UL Recognized RoHS Compliant CSA Certified





defaultTaxonomyAttributeLabel

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage Rating 40 A Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Top fuse status indicator Release characteristic Other **Utilization category** aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 14 x 51 mm Class Class aR Clearing (I2T) 750 Watt losses 8 W Fuse shape Cylindrical

Pre arc (I2T)

Used with

Finger safe holders/blocks and striker

84

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720025 FWP

White

Interrupt rating

200 kAIC

Fitted with:

Striker

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A14FI



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia