
Eaton FWP-40A22FI

Catalog Number: FWP-40A22FI

Eaton Bussmann series FWP high speed fuse, 700 Vac, 700 Vdc (UL), 40A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, With Indicator, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceremic





Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWP-40A22FI

UPC

051712542883

Product Length/Depth

EAN

5027590500746

Product Height

23 mm

Product Width

23 mm

58 mm

Product Weight

62.6 g

Warranty

Not Applicable

Compliances

CE Marked

RoHS Compliant

Certifications

UL Recognized





defaultTaxonomyAttributeLabel

Type

High speed fuse

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Amperage Rating

40 A

Accessories

JM70100 Fuse base

Breaking capacity

200 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Fuse indicator

Top fuse status indicator

Release characteristic

Other

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

22 x 58 mm

Class

Class aR

Clearing (I2T)

960

Watt losses

12 W

Fuse shape

Cylindrical

Pre arc (I2T)

68

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Used with

Finger safe holders/blocks and striker

Color

White

Interrupt rating

200 kAIC

Fitted with:

Striker

Connection

Ferrule end x ferrule end

Construction size

22 mm x 58 mm

Material

Ceramic

Packaging type

Standard

Quantity

10

Voltage rating

700 V

Fuse type

FWP-A22FI



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia